Docket No.: J1036.0016/P016

AMENDMENTS TO THE CLAIMS

- 1. (Currently Amended) Equipment (1; 100) for printing on non-woven-fabric, comprising a support (2; 102) driven such as to transport a sheet-(T) of non-woven-fabric, at least one driven printing body (3; 103) in order to carry out the printing and a control and command unit (6) operatively connected with each of said support and at least one printing body such as to detect electrical signals originating from said support and at least one printing body, turn said signals into numerical values representative of the status of their angular speed and torque moment, compare said numerical values with ratios of preset numerical values of said angular speed and said torque moments and send signals to said support and at least one printing body in order to correct any possible variations in said values which fall out with said ratios.
- 2. (Currently Amended) The equipment (1; 100) according to claim 1, wherein said support (2; 121) is driven by means of a motor (2M) and wherein said at least one printing body (3; 103) is driven by a motor (3M).
- 3. (Currently Amended) The equipment (1; 100) according to claims 1 or 2 claim 1, wherein said driven support (2; 102) is provided with through holes (21; 121) which cooperate with holding means (4) in order to hold the sheet of non-woven-fabric (T) onto said support.
- 4. (Currently Amended) The equipment (1) according to any of the claims 1 to 3 claim 1, wherein said support (2) is a cylindrical support represented by a press roller.
- 5. (Currently Amended) The equipment (100) according to any of the claims 1 to 3 claim 1, wherein said support (102) is a press belt.

- Docket No.: J1036.0016/P016
- 6. (Currently Amended) The equipment (100) according to claim 5, wherein said press belt (102) is a perforated belt closed on itself.
- 7. (Currently Amended) The equipment (1; 100) according to any of the claims 1 to 6 claim 1, wherein said at least one printing body (3; 103) comprises from two to twelve rotating engraved rollers operated individually and independently by motors (3M).
- 8. (Currently Amended) The equipment (1 ; 100) according to any of the claims 3 to 7 claim 3, wherein said holding means (4) comprise suction fans having the function of sucking air from the outside of the support (2; 102) towards its inside through said through holes (21; 121).
- 9. (Currently Amended) The equipment (1; 100) according to claim 8, wherein said suction fans (4) are represented by fans.
- 10. (Currently Amended) The equipment (1; 100) according to claim 8, wherein said suction fans (4) are represented by pumps of the compressor or vacuum pump type.
- 11. Currently Amended) The equipment (1; 100) according to any of the claims 8 to 10 claim 8, wherein said suction fans are connected to a water separator (5).
- 12. (Currently Amended) The equipment(1; 100) according to claim 11, wherein said separator (5) is a condenser.

- 13. (Currently Amended) The equipment (1; 100) according to claim 11, wherein said separator (5) separates the water from the air by mechanical and physical action.
- 14. (Currently Amended) The equipment (1; 100) according to claim 13, wherein said separator is a coclea-shaped distillator.
- 15. (Currently Amended) The equipment(1; 100) according to any of the claims 1 to 14 claim 1, further comprising guide means (A, B, C, D, E, F) suitable to guide and support the inlet and outlet sheet (T) of non-woven-fabric from said equipment.
- 16. (Currently Amended) The equipment (1; 100) according to claim 15, wherein said guide means (A, B, C, D, E, F) are rollers individually and independently motor-driven by corresponding motors (AM, BM, CM, DM, EM, FM).
- 17. (Currently Amended) The equipment (1;100) according to claims 15 or16 claim 15, wherein at least one pair (B, C) of said guide means are positioned at the ingoing non-woven-fabric into the printing stations and consist of widening means which allow increasing the height of the non-woven-fabric.
- 18. (Currently Amended) The equipment (1; 100) according to any of the claims 1 to 17 claim 1, further comprising an image acquiring device (7).
- 19. (Currently Amended) The equipment(1; 100) according to claim 16, wherein said device (7) is a camera or a video camera.

- 20. (Currently Amended) The equipment (1; 100) according to any of the claims 18 to 19 claim 18, wherein said device (7) is a digital device.
- 21. (Original) A process for the printing of non-woven-fabric comprising the steps of:

providing a non-woven-fabric sheet;

providing an equipment for printing on non-woven-fabric comprising a driven support for the transportation of said non-woven-fabric and at least one driven printing body;

feeding said equipment with said non-woven-fabric sheet;

performing the printing on said non-woven-fabric under the control and command of a control and command unit,

wherein said control and command unit is operatively connected with said support and at least one printing body such as to detect electrical signals originating from said support and at least one printing body, turning said signals into numerical values representative of the status of their angular speed and torque moment, comparing said numerical values with ratios of preset numerical values of said angular speeds and said torque moments and sending signals to said support and at least one printing body in order to correct any possible variations of said values which fall out with said ratios.

22. (Original) The process according to claim 21, wherein said control and command unit acts separately and independently on each motor which operates the corresponding rotating body of the equipment such as to make reference to the same electrical axis.

- Docket No.: J1036.0016/P016
- 23. (Currently Amended) The process according to claims 21 or 22 claim 21, wherein the control by the control and command unit is implemented thanks to by additional closed loop automatic control comprising the assistance of an image acquiring device.
- 24. (Currently Amended) The process according to any of the claims 21 to 23 claim 21, further comprising an operation stage of holding means in order to hold the non-woven-fabric sheet onto the outer surface of the support.
- 25. (Original) The process according to claim 24, wherein said operation stage of the holding means is achieved by suction fans which, by sucking air from the outside towards the inside of the support through through holes, hold the non-woven-fabric onto said support.
- 26. (Currently Amended) The process according to any of the claims 24 to 25 claim 24, also comprising a control stage of the operation of the holding means by said control and command unit.
- 27. (Currently Amended) The process according to any of the claims 25 to 26 claim 25, comprising a separation stage of the water from the air sucked in by the suction fans.
- 28. (Currently Amended) The process according to any of the claims 21 to 27 claim 21, wherein the printing stage occurs by means of flexographic (ink) or serigraphic (coloured colored paste) methods.

- 29. (Currently Amended) The process according to claim 28, comprising a dye control stage by the control and command unit through the optimisation optimization of the characteristics of each dye, such as flow, pressure and viscosity, depending on the type of non-woven-fabric to be printed.
- 30. (Currently Amended) The process according to any of the claims 21 to 29 claim 21, comprising a widening stage in order to ensure the maintenance of the product height.
- 31. (Currently Amended) The process according to any of the claims 21 to 30 claim 21, wherein printing takes place at a speed of up to 400 m/min on a sheet of wet or dry non-woven-fabric.
- 32. (Currently Amended) Non-woven-fabric obtainable by means of the process according to any of the claims 21 to 31 claim 21.
- 33. (Currently Amended) The non-woven-fabric according to claim 32 characterised characterized by having multicolour multicolour text and/or drawings.
- 34. (Currently Amended) Equipment (1; 100) for printing on non-woven-fabric, comprising a driven support (2; 102) provided with through holes (21; 121) so as to transport a sheet (T) of non-woven-fabric, at least one driven printing body (3; 103) for implementing the printing and driven holding means (4) which interact with said support in order to hold said sheet (T) onto said support (2; 102).